



Stealth High Powered Quiet Drying System Specifications

Center Band Sound Frequency	63 Hz	125Hz	250 Hz	500 Hz	1,000Hz	2,000 Hz	4,000 Hz	8,000 Hz	Total Sound 60 Hz Results	
Final Sound Pressure Level	55.3	60.4	71.9	80.3	78.5	76.7	72.5	65.4	84.2	dBa at Q=1, 5 feet
Final Sound Pressure Level	49.3	54.4	65.9	74.3	72.5	70.7	66.5	59.4	78.2	dBa at Q=1, 10 feet
Final Sound Pressure Level	45.8	50.9	62.4	70.8	69	67.2	63	55.9	74.7	dBa at Q=1, 15 feet
Final Sound Pressure Level	43.3	48.4	59.9	68.3	66.5	64.7	60.5	53.4	72.2	dBa at Q=1, 20 feet
Final Sound Pressure Level	41.3	46.4	57.9	66.3	64.5	62.7	58.5	51.4	70.2	dBa at Q=1, 25 feet
Final Sound Pressure Level	39.8	44.9	56.4	64.8	63	61.2	57	49.9	68.7	dBa at Q=1, 30 feet
Final Sound Pressure Level	38.4	43.5	55	63.4	61.6	59.8	55.6	48.5	67.3	dBa at Q=1, 35 feet
Final Sound Pressure Level	37.3	42.4	53.9	62.3	60.5	58.7	54.5	47.4	66.2	dBa at Q=1, 40 feet
Final Sound Pressure Level	36.2	41.3	52.8	61.2	59.4	57.6	53.4	46.3	65.1	dBa at Q=1, 45 feet
Final Sound Pressure Level	35.3	40.4	51.9	60.3	58.5	56.7	52.5	45.4	64.2	dBa at Q=1, 50 feet
Final Sound Pressure Level	34.5	39.6	51.1	59.5	57.7	55.9	51.7	44.6	63.4	dBa at Q=1, 55 feet

Sound pressure values are approximated from AMCA 300 Reverberant sound room total sound power values

* all information provided through **the new york blower company** via tests performed in their La Port IN sound lab, January 15th 2018